

Photon OD63T

Outdoor 5G CPE EG89B6T Datasheet

Baicells
Connect More with Less



INTRODUCTION

Baicells 5G outdoor CPE supports two network architectures, 5G Standalone (SA) and non-Standalone (NSA), with faster transmission speed, better bearing capacity and lower network delay.

The CPE supports 5G Sub6 band access to base station, LAN side provides RJ45 Ethernet interface, can connect with external Wi-Fi router to providing perfect experience for customers in laptop, gateway, industrial monitoring, telemedicine, unmanned aerial vehicle (UAV), virtual reality and immersive experience (VR and AR).

The product comes with a standard one-year warranty; an extended warranty is available.

HIGHLIGHTS

NOTE: Features can vary based on model or region.

- 5G SA/NSA Dual mode
- Supports NR Bands
N1/N3/N5/N7/N8/N20/N28/N38/N40/
N41/N66/N77/N78n
- Supports TDD Bands
B38/B40/B41/B42/B43
- Supports LTE FDD Bands
B1/B3/B5/B7/B8/B20/B28/B32
- Complies with 3GPP Release 16 standards
- 1000 Mbps Ethernet interface
- Peak data rate of up to NR SA DL 4670 Mbps, UL 1250 Mbps; NR NSA DL 5470 Mbps, UL 1350 Mbps
- 256QAM for DL and 256QAM for UL as the highest order modulation formats.
- Built-in directional 5G antennas
- GUI-based local and remote Web management
- Excellent Non-Line-of-Sight (NLOS) coverage
- Supports TR069 network management protocol
- Cell lock, SIM lock, and pin lock
- User-friendly LED status indicators
- Transparent bridge mode (L2 Support).

TECHNOLOGY

Standard	3GPP Release16
Mode	TDD/FDD
Channel Bandwidth	5~100 MHz
Multiplexing	LTE: DL 2x2 MIMO NR: DL 4x4 MIMO, UL 2x2MIMO
Security	Firewall: IP/MAC/URL filter; ACL rule

INTERFACE

Ethernet Interfaced	1*RJ-45 port 10/100/1000 auto-sensing, auto-MDX, WAN/LAN
Protocols Used	IPv4/IPV6, UDP, TCP, IP, ICMP, SNMPv2c, SNMPv3c, HTTPS, SSH, TELNET, TR069, TR104, CBSD
Network Management	Web GUI, ACS, OMC, SNMP
VLAN	802.1Q

PERFORMANCE

Peak Rate		DL (Mbps)	UL (Mbps)
	NR SA	Max. 4670	Max. 1250
	NR NSA	Max. 5470	Max. 1350
	LTE	Max. 1600	Max. 200
Modulation	DL: QPSK, 16QAM, 64QAM, 256QAM UL: QPSK, 16QAM, 64QAM, 256QAM		
Carrier Aggregation	LTE: Up to 5DL / 2UL EN-DC: Up to LTE 4DL + FR1		
Transmit Power	Power Class 3 (23dBm±1.5dBm) for LTE Bands Power Class 3 (23dBm±1.5dBm) for NR Bands Power Class 2 (26dBm±1.5dBm) for N41		
Receive Sensitivity	N41 (100MHz), -85dBm		

FEATURES

Photon OD63T

Outdoor 5G CPE EG89B6T Datasheet

Network Mode	NAT or Bridge
SIM	PIN management, SIM lock
Network Connection	Auto or manual
LTE Scan Mode	Full band scan or frequency lock
VPN	L2TP L2/L3, GRE L2/L3
NAT	Port forwarding, port trigger, DMZ, ALG
Diagnostics	TCP dump, ping, traceroute
Statistics	LTE status; connection/system up time; device status; DHCP client list; firewall status
Maintenance	Date and time setting; reboot; restore factory settings; restore or back up configuration file; firmware upgrade locally or OTA

LINK BUDGET

Antenna Type	Internal directional , 2T4R
Antenna Gain	2~8 dBi

PHYSICAL

LED Indicators	Power, WLAN, Internet, Cellular
USIM	1.8V/3V 4FF
Restore Button	Press for 10 seconds to restore the CPE to its factory settings
WPS Button	Press for WPS or Easy Mesh* configuration
Power Switch	Push 1.5s for ON/OFF
Temperature	- Operating Temperature: -40°C to 55°C - Storage Temperature: -40°C to 70°C
Humidity	5%~95%
Power Consumption	<20 W
Power Supply	- With POE Adaptor: - INPUT 100-240VAC - OUTPUT 24VDC 0.5A
Weight	About 23oz / 660g
Dimension	9.5 x 6.0 x 3.4 inches / 242 x 152 x 86 millimeters

NOTE: Customized versions can be requested.

Photon OD63T

Outdoor 5G CPE EG89B6T Datasheet



* Planned for future release